

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification:

A01K 89/00 // 89/015

A1

(11) International Publication Number:

WO 99/29168

(43) International Publication Date:

17 June 1999 (17.06.99)

(21) International Application Number: PCT/SE98/02227

(22) International Filing Date: 7 December 1998 (07.12.98)

(30) Priority Data:

9704559-5 8 December 1997 (08.12.97) SE

(71)(72) Applicant and Inventor: LUTTEMAN, Anders [SE/SE];
Sjögatan 34 A, S-591 30 Motala (SE).(74) Agent: TMP TRADEMARK & PATENT HB; Sättra Ängsgård,
S-590 54 Sturefors (SE).

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published


With international search report.

In English translation (filed in Swedish).

(54) Title: DEVICE FOR A SPINNING REEL

(57) Abstract

The invention relates to a device for a spinning reel for increasing the flying distance with light-weighted sinkers. The spinning reel comprises in a known way a reel frame body (1) with first and second side frames (2, 3) and a spool (5). The device includes a thumb key (10) running in slots (12) in the side frames (2, 3) and is sideways guided by these. In a first moment, before cast, the thumb key (10) is moved to a front position in the slots (12) and acts on a lever (16) arranged on a cover (6), said lever having a lower carrier pin (17) which puts a first branch (21) on a spring means (20), wound around a shaft (19), inbetween taps (9) axially projecting at the periphery of a flange (8) on the spool (5). Simultaneously the spool is released from the crank mechanism and can rotate freely. In a second moment the thumb key is pressed, whereby a carrying pin (13), disposed on the under side of the thumb key, is moved inbetween the taps (9) and when the thumb key in a third moment is drawn backwards rotates the spool in the reverse direction and gives the spring means (20) desired bias.



BEST AVAILABLE COPY

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Device for a spinning reel.

The present invention relates to a device for a spinning reel designed to give the spool an initial acceleration, said spinning reel comprising a reel frame body with first and second side frames, means keeping the side frames together, a cover over the first side frame, a cup covering the cover and the first side frame, a spool journaled in the side frames of the reel frame body, devices for operating the reel and a spring means

Modern spinning reels are very smoothrunning as they generally are provided with high quality bearings in all rotating parts. All parts affecting operation and performance in the casting moment are in most cases made of high quality, light material. To achieve large flying distance with heavy sinkers does not cause many problems since the kinetic energy absorbed to spin up the line-filled spool is relatively small compared to the total amount of kinetic energy of the sinker.

Using light-weighted sinkers drastically reduces the flying distance as a great deal of the kinetic energy of the sinker is used to start the spool filled with line. The spools in modern casting reels are as light as can be achieved without jeopardising the strength and operation. However the line on a filled spool has a relatively big mass whose centre of gravity is located at a greater distance from the rotation axis than the mass of the spool does, which is a condition that is difficult to do something about. Therefore a spool filled with line has a large momentum of inertia that takes great deal of the kinetic energy in the initial stage, the so-called "spin-up" process, and thereby reduces the initial velocity of the sinker and the casting length is reduced. It becomes naturally to consider how the initial moment of the casting could be affected so that the initial velocity of the sinker would not be reduced by the moment of inertia of the spool filled with line.

U. S. 4,881,697 discloses several solutions of devices for forcibly rotating the line spool on a spinning reel. All the solutions are based on that the operator manually stretches a spring that is released at the moment of casting and via a gear affects the axis of the line spool. Both torsion spring and compression spring are

suggested in the solutions. In all cases the spring force is transferred to the spool via a segmented gear, which releases the spool for rotation after the spring has transferred the energy to the spool. Some of the solutions suggested involves an extra manual operation to stretch the spring by operating a lever outside the reel or, like in a suggested solution, press a bar against a compression spring, whereby a linear segment gear on the bar transfers the spring energy to the axis of the spool.

However in the solutions suggested the spool has to be released from the crank mechanism by a first manual operation and after this the spring is stretched by a second manual operation to a stop position. The spool is prevented from being rotated by the stretched spring before casting is performed with a third manual operation when the thumb is released from the spool filled with line.

Thus the device creates a casting routine with more manual operations than is normal and no possibility to easily have an influence of how much the spring is stretched. The situation with short casts from shores with reeds and bushes requires that the tension of the spring is different from that of maximum casting range. It is thus a need to easily and quickly changing the spring tension.

No other effective and rational solutions not requiring altered casting routine are known and an object of present invention is therefore to provide a device giving the line spool on a spinning reel a contribution of a desired amount of acceleration in the moment of casting without executing any additional manual operations and without any other operating means than those normally existing and that the line spool is released from the crank mechanism and hold back in a normal way by means of the usually existing thumb key.

Another object is to provide a simple device by means of which the contribution of acceleration can be adapted to different weights of the sinker.

These objects are achieved by a device having the characteristics given in claim 1 and the subsequent claims.

Preferred embodiments of present invention will be explained more in detail below with reference to the accompanying drawings, on which:

Fig. 1 shows a fragmentary plan view of a spinning reel from behind

Fig. 2 shows a perspective fragmentary view of a spinning reel,

Fig. 3a – 3d show side views in a section A – A of an operating sequence at cast,

Fig. 4 shows a first adjusting device for changing of the spring tension

Fig. 5 shows a second adjusting device for changing of the spring tension

In fig. 1 is shown a fragmentary plan view of a spinning reel 1, which comprises a first side frame 2 and a second side frame 3, kept together by a plurality of transversal columns 4. Between the side frames is a spool 5 disposed, journaled in bearings in respective side frame. The first side frame has a cover 6 and over the cover and the side frame is a cap 7 applied. A flange 8 on the spool, facing the first side frame 2, is provided with axially projecting taps 9, evenly distributed along the periphery.

Between the first and second side frames 2 and 3 and laterally guided by them, a thumb key 10 is running. The thumb key has in its front part sideways projecting guiding pins 11 (visible in fig. 2) running in peripherally located slots 12 inside respective side frame. The thumb key has a cupped or open central part to provide a good grasp for the thumb on the casting hand. (see fig. 3a – 3d). In the back part a carrier pin 13 is projecting, downwardly directed towards the row of taps 9 on the flange of the spool and towards its center shaft. The thumb key is kept in an upper position by a spring 14 acting against the first side frame of the reel frame body 1, permitting the carrier pin 13 to get clear of the taps 9.

A lever 16 is journaled on a shaft 15, mounted in the cover 6. The lever has a lower carrier pin 17 projecting underneath the row of taps 9 on the periphery of the spool. An upper carrier pin 18 projects inwardly, in front of the front edge of the thumb key 10. On a second shaft 19, mounted in the cover, obliquely and close to the center shaft of the spool, is a coil spring 20 wound. The spring has a first branch 21, the end of which is disposed near the inside of the taps 9 and resting

against the lower carrier pin 17 on the lever 16 and keeps this against a stopper 22 (see fig. 3a – 3d), projecting from the inside of the cover 6. A second, shorter and diametrically inwardly bent branch 23 (see fig. 3a – 3d) on the spring 20 is put into a diametrical slot in the second shaft 19 to prevent the spring from rotating on the shaft.

In the operation sequence in fig. 3a to 3d is shown how the thumb key is moved to a front position and pushes the upper carrier pin 18 forward, whereby the lever rotates and by means of the lower carrier pin 17 moves the end of the longer branch 21 on the spring 20 in between the taps 9 at the periphery of the flange 8 on the spool 5. Simultaneously the spool is released from the reel crank gear unit by an existing mechanism in the reel, which is not shown. In fig. 3b is shown how the thumb key 10 is pressed down and the carrier pin 13 in the back part of the thumb key is moved in between the taps 9 at the periphery of the flange 8 on the spool 5.

Fig. 3c shows the situation when the thumb key 10, in a pressed down position, has been moved to a rear position at the rear ends of the slots 12. The rear position can be chosen by the operator anywhere between the initial position and the rear ends of the slots 12. It depends on what initial acceleration the operator wishes to add to the spool at casting. Fig. 3d finally shows how the thumb key is released whereby the longer branch of the spring 20 transfer its energy to the spool and give this an initial acceleration, which results in that the kinetic energy of the sinker is not absorbed by spinning up the line-filled spool. Existing, not shown mechanisms in the reel bring the thumb key in a known way back to its starting position and engages the gear unit between crank and spool when the crank is operated.

To enable adapting of the acceleration to different sinker weights, the bias of the spring 20 can be changed in two further embodiments of the invention by that the second shaft 19, around which the spring is wound and attached to, can be rotated with means operated from outside the cap 7.

These preferred embodiments are evident from fig. 4 and 5, in which two variations of adjustment devices are shown.

The first preferred embodiment is shown in fig. 4 in a partial view of a section of the cap 7 where a shaft 25, journaled in a bushing 26 in the outer wall of the cap has a chisel formed inner end (not visible) entering a diametrical slot 27 in the outer end of the second shaft 19 (the slot is visible in fig. 2).

The shaft has a flange 28 and between this and the cap 7 a pressure spring is applied, which keeps a knob 30, placed on the outer end of the shaft, pressed against the cup.

The contact surfaces between the cap 7 and the knob 30 are designed to catch the knob and the shaft in a desired position but permit rotating them with the fingers to adjust the bias in the spring 20.

The second preferred embodiment is shown in fig. 5 where a lever is fixed to the outer end of the second shaft and projects backwards, out through the cup. A slot (not shown) in the cap 7 is provided with step-by-step locking positions where the lever can be put in desired position to affect the bias in the spring 20.

Claims

1. Device for a spinning reel designed to give the spool an initial acceleration, said spinning reel comprising a reel frame body (1) with first and second side frames (2, 3), means (4) keeping the side frames together, a cover (6) on the first side frame, a cup (7) covering the cover and the first side frame, a spool (5) journaled in the side frames of the reel frame body, devices for operating the reel, and a spring means (20), characterised in that a flange (8) on the spool (5), adjacent to the first side frame (2) on the reel frame body (1), along its periphery has axially projecting taps (9) with even partition, that the spring means (20) is wound around a first shaft (19) fixed in the cover (6), that the spring means (20) has a first branch (21) projecting parallel to the flange (8) and a second diametrically inwardly bent branch (23), attached to the first shaft (19) and that the first branch (21) in a starting position rests against a lower carrier pin (17) on a lever (16), rotatably attached on a second shaft (15) in the cover (6) and which lever has an upper carrier pin (18), that a thumb key (10), guided sidewardly between the first and second side frames of the reel frame body, has guiding pins (11) sliding between front and rear end positions in slots (12) in the side frames and that the guiding pin (11) at the first side frame is in contact with the upper carrier pin (18) on the lever, that the rear part of the thumb key (10) on its underside has a carrier pin (13) above the taps (9) and directed towards the center shaft of the spool, whereby when the thumb key in a first moment is moved forward against the first carrier pin, the lever (16) rotates around the second shaft (15) so that the lower carrier pin (17) moves the end of the first branch of the spring means (20) in between the taps (9) at the periphery of the flange (8) of the spool and when the thumb key (10) in a second moment is pressed, the carrier pin (13) is likewise moved in between the taps (9) rotating the spool in the reverse direction in a third moment when the thumb key (10) is moved backwards, so that the spring (20) is given desired tension before a fourth moment when the thumb key is released and casting is carried out.

2. Device according to claim 1, characterised in that the first shaft (19) is rotatably attached in the cover (6) for adapting the bias of the spring means (20) to different sinker weights.
3. Device according to claim 2, characterised in that the shaft (19), by a knob lockable against the cup, can be rotated from outside the cup (7) by a third shaft (25) journaled in the cup (7) to give the spring means (20) desired bias.
4. Device according to claim 2, characterised in that the shaft (19) by a lever (31) applied on its end and projecting through the periphery of the cup (7), can be rotated from outside to give the spring means (20) desired bias.

Fig 1




Fig 2




Fig 3a




Fig 3b




Fig 3c




Fig 3d




Fig 4





Fig5



INTERNATIONAL SEARCH REPORT

International application No.

SE 98/02227

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: A01K 89/00 // A01K 89/015

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: A01K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPODOC

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4881697 A (K. KANEKO), 21 November 1989 (21.11.89), abstract --	1,2
A	Patent Abstracts of Japan, Vol 13, No 326, C-620 abstract of JP 1-104124 A (DAIWA SEIKO INC), 21 April 1989 (21.04.89), figure, abstract --	1,2
A	US 4762290 A (M. EMURA ET AL), 9 August 1988 (09.08.88), figure 8, abstract --	1
A	US 3612436 A (H.G. SHAKESPEARE), 12 October 1971 (12.10.71), abstract --	1

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

21 January 1999

Date of mailing of the international search report

02-02-1999

Name and mailing address of the ISA/

Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM

Authorized officer

Filip von Friesendorff

INTERNATIONAL SEARCH REPORT

International application No.

P SE 98/02227

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	SE 340383 B (B BOCKING ET AL), 15 November 1971 (15.11.71) --	1
P,A	EP 0813810 A2 (DAIWA SEIKO INC.), 29 December 1997 (29.12.97), column 1, line 54 - column 2, line 38 --	1
A	US 5601246 A (H. TAKAHASHI), 11 February 1997 (11.02.97) -- -----	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

01/12/98

International application No.

SE 98/02227

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4881697 A	21/11/89	JP 1104124 A JP 1849791 C	21/04/89 07/06/94
US 4762290 A	09/08/88	JP 62267679 A	20/11/87
US 3612436 A	12/10/71	NONE	
SE 340383 B	15/11/71	DE 1507060 A NL 6506918 A	03/04/69 02/12/65
EP 0813810 A2	29/12/97	JP 10004837 A	13/01/98
US 5601246 A	11/02/97	JP 7231739 A	05/09/95

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record.**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☒ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.